



Technical Data Sheet

Galtec Slicksol

GENERAL DESCRIPTION

SLICKSOL is a premium quality solvent emulsion degreaser and is supplied as a ready to use product. It can be applied manually through low pressure spray wash equipment. Removes oil and grease from engines, components, tools, floors and machinery. Also removes tar and bitumen.

DIRECTIONS FOR USE:

Apply **SLICKSOL** neat to dry surface to be cleaned by brush, dip tank, cloth or low pressure sprayer. Do NOT dilute with water. Leave in contact for a few minutes to allow the product to penetrate the soiling. Rinse off with water or blow off with air hose. **SLICKSOL** is not suitable for use through high pressure washers. Avoid contact with rubber.

PRODUCT INFORMATION:

Appearance	:	Clear blue liquid
Density at 20°C (Typical)	:	0.82 kg/l
Flash point (Typical)	:	>61°C
Emulsion characteristics	:	Quick break

HANDLING AND SAFETY:

Please refer to product Material Safety Data Sheet.

SIZES:

SLICKSOL is supplied in 4x5 litre cases, 25 litre and 200 litre drums.

USE OF THIS TECHNICAL DATA SHEET

This Technical Data Sheet complements and should be used in conjunction with the appropriate Safety Data Sheet. The information and recommendations given above are, to the best of the company's knowledge and belief, accurate and reliable as of the date issued, but are offered without guarantee or warranty and do not form part of any specification, except where otherwise stated. They are given solely for guidance in appropriate handling and use of the material. They relate to the specific material designated and may not be valid for such material used in combination with any other material or in any process. Conditions of use of the material are under the control of the user, therefore it is the user's responsibility to satisfy himself as to the suitability of the material, and the suitability and completeness of this information, for his own particular use.